

OPERATING CONDITIONS	S-1	S-2	S-3	S-4	S-5
FLIGHT LEVEL	370	350	410	390	330
LANDING WEIGHT (X1000)	130	150	135	155	125
DESCENT TYPE	.80M/ 250	.80M/ 280/250	.80M/ 320/250	.80M/ 350/250	.80M/ 320/250

FIGURE 86.—Descent Performance.

<b>.80M/250 KIAS</b>						<b>.80M/280/250 KIAS</b>					
FLIGHT LEVEL	TIME MIN	FUEL LB	DISTANCE NAM			FLIGHT LEVEL	TIME MIN	FUEL LB	DISTANCE NAM		
			AT LANDING WEIGHTS						AT LANDING WEIGHTS		
			120,000 LB	140,000 LB	160,000 LB				120,000 LB	140,000 LB	160,000 LB
410	27	1610	133	137	138	410	25	1550	123	129	132
390	27	1600	130	134	136	390	24	1540	121	127	130
370	26	1570	123	128	129	370	24	1520	115	121	125
350	25	1540	116	120	122	350	23	1500	111	117	120
330	24	1510	110	113	115	330	23	1480	106	111	115
310	23	1480	103	107	108	310	22	1450	100	105	108
290	22	1450	97	100	101	290	21	1430	94	99	102
270	21	1420	90	93	95	270	20	1400	88	93	95
250	20	1390	84	87	88	250	19	1370	83	87	89
230	19	1360	78	80	81	230	18	1350	77	81	83
210	18	1320	72	74	75	210	17	1310	72	75	76
190	17	1280	66	68	68	190	16	1280	66	69	70
170	16	1240	60	62	62	170	15	1240	61	63	64
150	14	1190	54	56	56	150	14	1200	55	57	58
100	11	1050	39	40	40	100	12	1080	42	42	42
050	8	870	24	24	24	050	8	870	24	24	24
015	5	700	12	12	12	015	5	700	12	12	12

  

<b>.80M/320/250 KIAS</b>						<b>.80M/350/250 KIAS</b>					
FLIGHT LEVEL	TIME MIN	FUEL LB	DISTANCE NAM			FLIGHT LEVEL	TIME MIN	FUEL LB	DISTANCE NAM		
			AT LANDING WEIGHTS						AT LANDING WEIGHTS		
			120,000 LB	140,000 LB	160,000 LB				120,000 LB	140,000 LB	160,000 LB
410	22	1490	113	120	123	410	21	1440	106	112	116
390	22	1480	111	117	121	390	21	1430	103	110	114
370	21	1460	105	112	116	370	20	1420	99	106	110
350	21	1440	101	107	111	350	20	1400	95	101	106
330	20	1420	96	103	107	330	19	1390	91	98	102
310	20	1400	92	98	102	310	19	1380	88	94	98
290	19	1390	89	94	98	290	18	1360	85	90	95
270	19	1370	85	90	94	270	18	1350	82	87	91
250	18	1350	80	85	88	250	17	1330	78	83	87
230	17	1330	75	79	82	230	17	1310	74	78	81
210	17	1300	71	74	77	210	16	1290	70	74	76
190	16	1270	66	69	71	190	16	1270	65	69	71
170	15	1240	61	64	65	170	15	1240	61	64	66
150	14	1210	56	59	60	150	14	1210	57	60	61
100	12	1110	45	46	46	100	13	1130	47	48	49
050	8	870	24	24	24	050	8	870	24	24	24
015	5	700	12	12	12	015	5	700	12	12	12

NOTE: FUEL FOR A STRAIGHT-IN APPROACH IS INCLUDED

FIGURE 87.—Descent Performance Chart.